

## Product information | TECHNICAL DATA SHEET

### NITRO 2G COLORS

500ml, 14 Oz, 390 g

#### GENERAL DESCRIPTION

The Nitro 2G technology was designed to produce very fast-drying results, available in a range of high coverage colors. These paints are formulated with alkyd resins and matt finish pigments.

#### FEATURES

- High pressure.
- Very fast drying.
- Does not contain lead nor other heavy metals.
- Hardens well.
- Excellent flexibility.
- Excellent coverage.
- Silver Killer (covers metallic paints).
- Great pigment durability.
- Strong resistance to abrasion once the film is polymerized.
- Easy to apply and repaint.
- Excellent resistance to the sun and rain.
- Very good resistance to UV light (see chart).

#### APPLICATIONS

Due to the characteristics of this product, we recommend using it for final finishes. Since it is a high quality paint, it may also be used for an endless amount of jobs where its qualities are required.

- Industry
- Crafts
- Touch-ups
- DIY
- Road works
- Sign painting

#### INSTRUCTIONS FOR USE

- Shake the aerosol well before using, approximately for one minute after hearing the sound of the mixer.
- For best results apply in thin layers. Three thin layers are always better than one thick one, and may be repainted within ten minutes with the same paint.
- Turn the aerosol upside down to clean out the valve after use, if the nozzle becomes blocked replace it with a new one.
- Never apply to equipment that is plugged in and use in well ventilated areas.
- Request safety datasheets.

#### PHYSICAL PROPERTIES

Color:	See chart
Brillo 60° (ASTM D-523 ISO 2813):	<10%
Dry to the touch (ASTM D-1640 ISO 1517):	10'
Completely dry (ASTM D-1640 ISO 1517):	30'
Thickness of dry layer (ASTM D-823 ISO 2808):	20 µm/yers
Theoretical yield (continuous painting):	2.8 m²
Thinner:	Ethyl Acetate
Product life:	> 5 years
Second coat:	After 10'
Heat resistance of paint:	100°C
Condition for application:	Minimum room temperature 8°C
	Surface temperature 5°C a 50°C
	Max humidity . 85% R.H.P

\* All of the adherence tests have been carried out on steel plates.

#### CAUTION



#### APPEARANCE



#### COLORS

EX015A1021M	Light Yellow	EX015A0034M	Guacamole Green	EX015A0027M	Vampire Violet
EX015A2004M	Orange	EX015A0008M	Light Blue	EX015A0010M	White
EX015A3001M	Vivid Red	EX015A3013M	Marine Blue		

#### LABEL



#### CAP SYSTEM



#### PACKAGING

Nominal capacity 400ml.  
Heat resistance of packaging: <50°C  
Propellant: GLP C3-C4  
Pressure: High pressure  
Valve: Female

Box (6 units)  
205 X 140 X 200 mm.

