

## Product information | TECHNICAL DATA SHEET

**WATER BASED.** Water soluble, low pressure, odorless, matt finish and in & outdoor use.  
300 ml: 9.7 Oz, 277g. 100 ml: 3.1 Oz, 90g.

### GENERAL DESCRIPTION

Fast drying water based aerosol paint of excellent characteristics with a matt finish of high quality and long durability.

### FEATURES

- Low odor.
- Fast drying.
- Good adhesion.
- Excellent covering power.
- Totally lead and heavy metals free.
- Great durability on outdoor and indoor exposure, due to the great fastness to light of the pigments.
- Easy application and repainting.
- Soluble in water during the first minutes of drying. (10')
- Resistant to exterior and outdoor use (rain, washing, etc) once the paint has dried.
- Suitable for painting expanded polystyrene.

### INSTRUCTIONS FOR USE

- Shake properly the aerosol before using it for at least one minute after the agitator ball is free.
- Apply to clean and dry surfaces. On plastic using a primer may be necessary.
- Apply thin coats for best results. It is always better three thin layers than a thick one. Repaintable after thirty minutes with the same paint.
- Reverse the aerosol valve to purge after use, if the actuator gets blocked, replace it with a new one.
- Do not apply on connected equipments and use the product in well ventilated areas.
- Ask for safety data sheets.

### PHYSICAL PROPERTIES

Bonding agent:	Modified PU
Color:	See chart
Gloss 60° (ASTM D-1640 ISO 1517):	<10% matt
Touch Drying (ASTM D-1640 ISO 1517):	30'
Total Drying (ASTM D-1640 ISO 1517):	72 h
Thickness of dry layer (ASTM D-823 ISO 2808):	15-20 µ/capa
Adherence (ASTM D-3359 ISO 2409):	0 B
Theoretical yield (pintado en continuo):	2m² for 300 ml
Thinner:	Water and alcohols
Shelf life:	(Well Stored) 5 Years
Recoating:	After 30'
Condition for application:	Minimum room temperature 8°C Surface temperature 5°C a 50°C Max humidity 85% R.H.P
Heat painting resistance:	Undetermined

\* All of the adherence tests have been carried out on iron plates. Last date revision 11/03/2014

### CAUTION



### APPLICATIONS

The product can be used on many substrates: iron, steel, plastics, wood, directly on expanded polystyrene.

- Fine arts
- Graffiti
- DIY
- Crafts
- Industry
- Decoration

Furthermore, the pigments used have a great fastness to light, giving the finished color durability on outdoor exposure. Due to its low odor, thanks to its contents of water based resins, it becomes the ideal product for interior use in spaces with poor ventilation. A very non-harmful product but adult supervision is always recommended when being used by a child.

### APPEARANCE



### LABEL



### CAP SYSTEM



Suitable for profesional use and fine arts, we have attached more technical information about the product and the color.